

Clay Blocks are extruded & perforated by nature, bigger in sizes than bricks, are manufactured using modern methods. These are completely exposed with good compressive strength having horizontal perforations & non load bearing clay blocks. These Blocks are easy to install, highly stable & durable. No Plastering is required & perform exceptionally well in a variety of applications.

Features

- Eco Friendly
- Better Thermal & Sound Insulation
- Higher Compressive Strength
- Lower Water Absorption

Benefits

- Passive Fire Protection
- Thermal Insulation
- Cryogenic Insulation
- Long Life & Cost Saving

Advantages

- Acoustic Insulation
- Hot Surface Insulation
- Combination Solution
- Extra Protection & Natural Beauty

Technical Information

- * Compressive Strength 3.5N/m2. As per IS 1077-1992
 IS:3495 (Part 1-4) 1992 (Reaffirmed 2016)
 IS:1077 1992 (Reaffirmed 2021)
 - * Water Absorption 14.25% 14.5% as per IS



Model No - EB 01 Model Name - Filler Slab Dimension - 18" x 9" x 3" Weight: 8.5 KG

Qty per Sft: 0.9 Nos



Model No - EB 02 Model Name - Filler Slab Dimension - 24" x 9" x 3"

Weight: 11.5 KG Qty per Sft: 0.7 Nos



Model No - EB 03 Model Name - Clay Block Dimension - 16" x 8" x 4" Weight: 6 KG

Qty per Sft: 1.13 Nos



Model No - EB 04 Model Name - Clay Block Dimension - 16" x 8" x 6"

Weight: 11.5 KG

Qty per Sft: 0.88 Nos



Model No - EB 05 Model Name - Clay Block Dimension - 16" x 8" x 8" Weight: 14 KG

Qty per Sft: 0.88 Nos



Model No - EB 06

Model Name - Maruthi Blocks

Dimension - 14" x 10" x 3"

Weight: 5.33 KG Qty per Sft: 1 Nos



